




NEED A DEPENDABLE LUBE NO-FLOW FOR YOUR DIVIDER BLOCK SYSTEM?

**PROFLO JR. IS "EXACT RETROFIT FOR THE DNFT"
Cost Less - More Reliable - Better Features**

"Same Wiring Colors for Easy Installation"





II 2G EEx md II T5

Cl I; Zone 1; Ex md IIC T5
Cl I; Div 1; Grps. A,B,C,D; T5
KEMA 05ATEX2085 X Amb.-40°C...+85°C

proflo Jr. - DNFT COMPARISON



3 year full warranty ——— VS. ———→ 2 year warranty

3.3 volt hermetically sealed extended temperature battery ——— VS. ———→ 3.3 volt cordless phone battery

5 year battery warranty up to 10 year battery life ——— VS. ———→ NO battery warranty

Switch rated for 300 VDC & 120 VAC @ .5 amps ——— VS. ———→ Switch rated for 2.5VA 240 VDC ONLY

Patented captive magnet assembly— NO lost magnet, spring or spacer.....EVER ——— VS. ———→ Old technology magnet assembly, causes loss of magnet, spring or spacer during installation

Heavy duty magnet housing eliminates bending and failure ——— VS. ———→ Magnet assembly is easily bent due to thin wall of housing

Switch closure output standard with every unit. ——— VS. ———→ Switch closure output optional with added cost

Hall effect transistor activated "unlimited duty cycle" ——— VS. ———→ Uses mechanical reed switch "limited duty cycle"

Spring Tested to 20,000,000 Cycles---NO BROKEN SPRINGS

proflo Jr. "RELIABLE LUBE NO-FLOW SHUTDOWN"

Monitors Operation of CCT® - ALEMITE® - LINCOLN® - TRABON® - SB® - DROPSA® Divider Block Systems



3201 West Wall St.
Midland, Texas 79701
Office: 432-520-6700
Fax: (432) 520-6700

